

RS50

Silver Solar Control film

Product description

50µ silver solar control polyester film for internal use on windows.

Typical uses

Designed for flat-sided internal window applications such as office windows and rear windows of vans.
Designed for use up to 10 years when professionally installed.

Shelf life

2 years when stored in original packaging at 21°C and 50% RH.

Physical properties (Average Values)

Tests made at 23°C and 50%RH unless otherwise stated

Film thickness:	50 microns
Total solar energy rejected:	77.0%
Total solar energy reflectance:	52.0%
Total solar energy absorbance:	34.0%
Total solar energy transmittance:	14.0%
Visible light transmitted:	17.0%
Visible light reflected:	55.0%
Ultra violet light rejected:	97%
Shading coefficient:	0.27
Glare reduction:	80.68%

Application Data

For internal applications only.

Application surfaces must be scrupulously clean.

We recommend our special window film squeegee GT020 Unger snappable to make application easier.

Incorporates a tough scratch resistant coating aids installation and maintenance whilst increasing the life of the film.

All values for engineering parameters are determined by the manufacturers using independent and certified testing laboratories.

THIS PRODUCT CARRIES A FULL 10 YEARS MANUFACTURER'S WARRANTY WHEN PROFESSIONALLY INSTALLED.

All technical information is based on manufacturer's claims and is believed to be true at time of print but does not constitute a warranty. Due to the complexity of end use the purchaser should carefully consider the fitness and performance of the product for their own application or use.
We reserve the right to make changes to specifications without prior notice.

South Sales: T 01753 696977 | North Sales: T 01709 829800
Free Fax 0800 374635 | E sales@allprint.co.uk | W allprint.co.uk



All Print Supplies