

# DigiGuard TP7-20

## Textured clear rigid PP laminate

### Product description

A matt textured scratch resistant indoor over laminating film.

Product features a pure acrylic based pressure sensitive adhesive backed with a 70gsm single-side PE coated siliconised Kraft liner.

---

### Typical uses

Totally PVC free, ideal for use in applications where PVC or phthalate containing products are not permitted.

Suitable for indoor use.

For the protection of inkjet prints.

The matt textured surface gives a good degree of protection to mechanical wear and tear as well as preventing glare caused by reflection from strong light sources.

---

### Shelf life

2 years when stored in original packaging at 21°C and 50% RH.

---

### Physical properties (Average Values)

Tests made at 23°C and 50%RH unless otherwise stated

**Film thickness:** 140 ± 5 microns

**Adhesive Thickness:** 25 micron

**Liner weight:** 75gsm

**UV block (UVa):** 20%

**Temperature ranges:** Application Range: plus 2°C to plus 30°C

**Peel Values:** 20min/180° - 10-12 N/25mm (Direct to S/S)

**Fire rating:** Product based on polypropylene, no fire certificate.

---

### Application Data

Product is predominantly for indoor use only. However, it can be used externally for selected short-term applications depending on location.

To ensure good bond strength, product must be applied to dry, clean, grease free surfaces.

Once laminated, leave the job for at least 4 hours to allow the adhesive to cure before trimming or rolling.

The use of a laminator, with no heat is recommended for applying this product to avoid any undue stress or stretching. We only recommend dry application.

It is essential to leave the print to thoroughly dry before applying the overlamine.

As a general rule, a minimum of 4 hours is recommended at normal room conditions.

At lower application temperatures this time may need to be extended.

The product can be used as a general purpose overlamine as well as for roll-up and pop-up graphics.

It is recommended for flat surfaces only and is not suitable for contours or 3D curves.

All technical information is based on manufacturer's claims and is believed to be true at time of print but does not constitute a warranty. Due to the complexity of end use the purchaser should carefully consider the fitness and performance of the product for their own application or use.

We reserve the right to make changes to specifications without prior notice.

---

**South Sales:** T 01753 696977 | **North Sales:** T 01709 829800

**Free Fax** 0800 374635 | **E** [sales@allprint.co.uk](mailto:sales@allprint.co.uk) | **W** [allprint.co.uk](http://allprint.co.uk)



All Print Supplies