

White faced magnetic PVC, 0.60mm

Product description

Flexible, isotropic magnetic sheet laminated on the face side with a gloss white vinyl.

Typical uses

Suitable for a range of both indoor and outdoor use.

For use as a temporary or replacement directional signage.

Shelf life

2 years when stored in original packaging at 21°C and 50% RH.

Must be stored on end, or suspended, due to weight of product.

Physical properties (Average Values)

Tests made at 23°C and 50%RH unless otherwise stated

Total thickness: 0.60mm ±0.1mm

Film thickness: 0.1mm ±0.1mm

Temperature ranges:

Application Range: plus 15°C to plus 30°C

Service Range: minus 20° to plus 45°C

Holding Force: >29g/cm².

Product will only adhere to ferrous surfaces such as iron or steel.

Non-ferrous metals such as aluminium will not work.

This product is NOT DESIGNED for use on the exterior of moving vehicles, use our 0.85mm magnetic for this application.

Application Data

Product must be applied to clean surfaces.

It is not designed to be applied to a surface and left for extremely long periods.

Regularly remove the sign and clean and lightly wax both the back of the sign and the paintwork. This helps avoid damage to the sign and paintwork and will facilitate easier ongoing removal of the sign.

Ensure that all areas of the sign are in firm contact with the surface before use, remove all air bubbles and only apply to flat or very slight 2D curves, such as vehicle sides. Failure to this could result in the loss of the sign.

Product can be rolled when not in use, however to avoid damage, it should be stood on end and wound with the graphic face out in a roll not less than 150cm in diameter.

Refer to our Product Portfolio, in Technical Information, or specific instruction sheet on best practices for using our magnetic sheet.

All technical information is based on manufacturer's claims and is believed to be true at time of print but does not constitute a warranty. Due to the complexity of end use the purchaser should carefully consider the fitness and performance of the product for their own application or use.

We reserve the right to make changes to specifications without prior notice.

South Sales: T 01753 696977 | **North Sales:** T 01709 829800

Free Fax 0800 374635 | **E** sales@allprint.co.uk | **W** allprint.co.uk



All Print Supplies